



NOTES~  
 1. OUTPUT 2.0 MV/VOLT NOMINAL  
 2. CAPACITY 10,000 & 20,000 IN. LBS.

25/64 DIA 8 HOLES - 2 PLACES  
 EQ SPACED WITHIN  
 .005 OF TRUE POSITION

PROPRIETARY DATA  
 The information contained herein is the property of Lebow Associates, Inc. and is to be used only for the purposes intended. No part of this information is to be reproduced or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage and retrieval system, without the prior written permission of Lebow Associates, Inc. The company does not apply to vendor proprietary parts.

DET. NO	PART NO	DESCRIPTION	REQ'D
<b>INSTALLATION DIMENSIONS ~ FLANGED REACTION TORQUE SENSOR</b>			
SCALE: FULL	DRAWN BY: T.A.	REV. D-101 B-13494	MAT'L: ~
DATE: 4-12-66	CHK'D BY:	MODEL: 2111-101	JOB NO: 2831
UNLESS OTHERWISE SPECIFIED:			
TOLERANCE ON FRACTIONS ± 1/64	TOLERANCE ON DRILLED HOLES + .007	REMOVE ALL BURRS & SHARP EDGES	
TWO PLACE DECIMALS ± .010	DIMENSION LIMITS HELD AFTER PLATING		
THREE PLACE DECIMALS ± .006	SURFACE FINISH 125		
ANGLES ± 0'30"			
<b>LEBOW ASSOCIATES, INC.</b> OAK PARK, MICHIGAN			DRAWING NO. <b>B-13493</b>

SYM.	REVISION	DATE